



OIL COUNTRY LATHES

STANDART MACHINE SPECIFICATION		Unit	C10T.10	C10T.12
CAPACITY	Height of centers	mm	400	
	Swing over bed	mm	800	
	Swing over cross slide	mm	560	
	Swing in gap	mm	990	
	Width of bed	mm	560	
	Distance between centers	mm	1500;2000;3000;4000;5000;6000	
	SPINDLE	Spindle nose DIN 55026 – ANSI B5.9	No	A20 – A2.20
Spindle bore		mm	260	315
Spindle taper		Metric	318	
HEAD STOCK	Number of spindle speeds		12	
	Spindle speed ranges	rpm	8-400 (10-480)	
	Main motor power	kw	11 (15)	
FEEDS	Number of feeds		152	
	Longitudinal feed range	mm/rev	0,039 – 15	
	Cross feed range	mm/rev	0,02 – 7,5	
THREADS	Number of threads		76	
	Metric thread range	mm	0,5 – 150	
	Inch thread range	Tpi	60 – 1/5	
	Module thread range	Module	0,125 – 37,5	
	DP thread range	DP	240 – 4/5	
CARRIAGE	Cross slide travel	mm	410	
	Top slide travel	mm	150	
TAIL STOCK	Quill diameter	mm	105	
	Quill taper	Morse	No.6	
	Quill travel	mm	225	
WEIGHT	For DBC 2000 mm	kg	6000	6100