


- Carbide tipped jaws for inside and outside measurements
- Resolution: 0.01mm/0.0005"
- Buttons: on/off, zero, mm/inch
- Automatic power off, move the digital unit to turn on power
- Battery CR2032, data output, meet DIN862
- Made of stainless steel
- Optional accessory: data output system



DATA OUTPUT

| Code        | Range         | Accuracy | Thumb roller | L   | а  | b    | С  | d  |
|-------------|---------------|----------|--------------|-----|----|------|----|----|
| 1110-150A*  | 0-150mm/0-6"  | ±0.03mm  | with         | 236 | 21 | 16   | 16 | 40 |
| 1110-200A*  | 0-200mm/0-8"  | ±0.03mm  | with         | 286 | 24 | 19   | 16 | 50 |
| 1110-300A*  | 0-300mm/0-12" | ±0.03mm  | with         | 400 | 25 | 20.5 | 17 | 60 |
| 1110-150AW* | 0-150mm/0-6"  | ±0.03mm  | without      | 236 | 21 | 16   | 16 | 40 |
| 1110-200AW* | 0-200mm/0-8"  | ±0.03mm  | without      | 286 | 24 | 19   | 16 | 50 |
| 1110-300AW* | 0-300mm/0-12" | ±0.03mm  | without      | 400 | 25 | 20.5 | 17 | 60 |

<sup>\*</sup>Supplied with manufacturer calibration certificate