



# Economical Type Rapid Index













5C COLLET INDEXER NON ECONOMICAL

0	3 JAW CHUCK VSC-4A, for VSI-4 / VSC-5A for
	VSI-5, the big range clamping capacity ø3 - ø100,
	it's better than collet fixing type.

- Simple & rapid operation.
- Dividual number 24-notch (15° each)
- Table scale 1°, for angular indexing.
- Table bore 30mm.
- Horizontal / vertical & 2 direction
- Suit for milling & drilling machine using.
- Optional: tailstock TS-1, Please see page A2


ORDER NO.	Α	В	С	D	E	kgs	CODE NO.
VSI-4	187	146	146	80	135	10.5	1001-064
VSI-5	202	161	161	87	142	14.5	1001-065



## Simple Rotary Chuck







VSR-6 WITH VPS-6A CHUCK VSR-8 WITH VPS-8A CHUCK

- 4-jaw chuck (include reversable and removable jaw) is designed with swivel base for multifunctional purpose.
- VERTEX simple rotary chuck can be placed and fixed on your desired position.
- 360° vernier scale: smooth swival motion and easy locking by screws.
- Both horizontal and vertical position could be used on milling and machining center.

ORDER NO.	A	A1	В	B1	С	D	F	G	н	1	J	К	М	kgs	CODE NO.
VSR-6	244.6	233.2	139.3	110.4	100	160	14.9	25	70.6	3-M8	69	28.9	14	18	1001-068
VSR-8	340	269.4	159	124.6	115	200	18.4	25	86	3-M10	75.7	34.4	18.4	30.5	1001-067


### Precision Universal Angle Chuck

VUA

### With VSC-4 Chuck



- Precision graduction for accurate reading.
- Its swivelling and tilting features with clamping make this unit well suited for straight or inclined surface, angular driling machining on various machine tools.
- With VSC-4 3-Jaw chuck.
- O.D. clamping Ø3-90 mm,
- I.D. clamping Ø32-84 mm.
- Tolerence ±0.01mm/100mm.
- 2 axis with angle scale
- For angle setting
- Chuck indexing / Rotating setting
- Tilting Features same as VUA series. Page B5



- Intilig I data of dame do Verroundi I -g										
RDER NO.	A	В	С	D	Е	F	G.W (kgs)	CODE NO.		
A-100J	180	77	181	112	110	16	14	2003-060		